

Miller 216WLS Manyard[®] Shock-Absorbing Lanyard



Description

The 216WLS Manyard Shock-Absorbing Lanyard is a “connecting device” for fall protection applications. The 216WLS features a special woven shock-absorbing inner core that reduces fall arrest forces. The heavy-duty tubular outer jacket serves as a back-up web lanyard. It features two locking snap hooks. Available in lengths from 4’ to 10’.

Materials

Webbing:

- Safety Strap/Jacket: Yellow tubular polyester web
- Shock-absorbing web core: polyester
- 1” elastic

Minimum Tensile: 5000 lbs. on webbing

Thread: 6 cord bonded 3 strand polyester thread, with a minimum tensile of 42 lbs.

Hardware: Steel Minimum Tensile strength

Locking Snap Hooks 5000 lbs. (22kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load: 310 lbs -140.62 kg

Label Materials: Valeron

Certification

OSHA 1926.502, 1910.66; ANSI A10.32; and CSA Z259.2.2 Type 1



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.