

Miller HP Series Non-Stretch Harnesses

Models: 650T Family

Materials

Webbing	1 3/4" Polyester
Minimum Tensile	5,000 lbs. (22kN) on webbing
Thread:	6 cord bonded 3 strand polyester thread. Minimum tensile of 42 lbs.
Label Pack:	Evoprene, Nylon
Labels:	Valeron
Grommets	Brass
Hardware	Steel Minimum Tensile strength
- D-Ring	5,000 lbs. (22kN)
- Buckles	4,000 lbs. (18kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load: 400 lbs (181.4 kg)

Certification

Meets OSHA 1926.502, ANSI A10.32, Z359.1 and CSA requirements.



650T-61
Shown

Model No.	Front D-ring	Side D-Rings	Shoulder D-Rings	Shoulder Strap	Leg Strap	Chest Strap	Special Features	Weight
650T/UGK	option	No	No	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	2.90 lbs. (1.3kg)
650T-3/UGK	option	No	Yes	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	5.00 lbs. (2.3kg)
650T-4/UGK	option	No	No	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	3.50 lbs. (1.6kg)
650T-7/UGK	option	Yes	No	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	3.50 lbs. (1.6kg)
650T-58/UGK	option	Yes	No	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	4.10 lbs. (1.9kg)
650T-61/UGK	option	Yes	No	Friction	Tongue	Mating	Shoulder pads, Back pad, Lanyard rings, Belt loops, Removable waist belt	5.10 lbs. (2.4kg)
650T-64/UGK	option	No	Yes	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	3.7 lbs. (1.7kg)
650T-76 /UGK	option	Yes	No	Friction	Tongue	Mating	6" (152mm) back pad, Tool belt, Shoulder pads, Pull-free lanyard rings, Belt loops	5.10 lbs. (2.4kg)
650T-77/UGK	option	Yes	No	Friction	Tongue	Mating	6" (152mm) back pad, Tool belt, Pull-free lanyard rings, Belt loops	5.00 lbs. (2.3kg)

MILLER®

by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.