

# Non Shock-Absorbing Rope Lanyard

## Models: 195R Series

### Description

The 195R is a non-shock-absorbing rope lanyard designed for positioning and restraint applications. The 195R is available in five unique models that utilize different rope diameters with either nylon or polyester rope.

### Materials

#### Rope Designations by Model:

195R-2 – 5/8" Spun Nylon

195R-3 – 3/4" Filament Nylon

195R-4 – 1/2" Filament Polyester

195R-5 – 5/8" Filament Polyester

195R-8 – 1/2 " Filament Nylon

**Splices:** A standard four-tuck splice is hand-crafted on each end with a tensile strength equal to that of the rope. The ends of the rope are seared to prevent fraying. The last splice is treated with a nylon-based stiffening agent to prevent the splice from unraveling.

**Thimbles:** A round, black plastic thimble is used in each lanyard eye to protect the eye from wear.

### Technical

**Max. Working Load:** 310 lbs (141 kg)

**Minimum Tensile:** 5,000 lbs (22kN)

### Sizes Available

25', 50', 75, and 100' lengths. Additional lengths are available upon request.

### Certification

Meets OSHA 1926.502, 1910.66, ANSI A10.32 and CSA Z259.2.2 Type 1 requirements.



**WARNING!**

**This product is to be used for positioning only, unless it is used in conjunction with a shock absorber.**

**MILLER**

by Honeywell

Toll Free 800.873.5242 (press 4) • [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com) • [www.millerfallprotection.com](http://www.millerfallprotection.com)

**WARNING!** THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.