Manyard[®] II Shock-Absorbing Lanyards w/Aluminum Connectors

Description

The Manyard II Shock-Absorbing Lanyards are connecting devices designed to reduce fall arrest forces. They feature a unique stretchable design that offers greater maneuverability and safety for the user by contracting 6 ft. [1.8m] to 4 ft. [1.2m]. Manyard II Lanyards greatly reduce the chances of tripping, snagging or dragging.

Materials

Webbing:

Safety Strap/Jacket: Green tubular polyester webbing

Shock-absorbing web core: polyester

1" elastic

Min. Tensile: 5,000 lbs. (22kN) on webbing

Thread: 6 cord bonded 3 strand polyester thread,

with a minimum tensile of 42 lbs.

Hardware: Aluminum

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Label Materials: Valeron

Technical

Max Working Load Capacity: 310 lbs (141 kg)

Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 ½ in. (63mm) gate opening





Certification

OSHA 1926.502, 1910.66 and ANSI A10.32

SKU	# of Legs	Harness Connection	Anchorage Connection	Weight	Standard Length*
216MAL/6FTGN	One	Aluminum Locking Snap Hook	Aluminum Locking Snap Hook	1.6 lbs (0.7kg)	6' (1.8m)
219MAL/6FTGN	One	Aluminum Locking Snap Hook	Aluminum Locking Rebar Hook	2.4 lbs (1.1kg)	6' (1.8m)
231MAL/6FTGN	Two	Aluminum Locking Snap Hook	Aluminum Locking Rebar Hooks	4.2 lbs (2.0kg)	6' (1.8m)
232MAL/6FTGN	Two	Aluminum Locking Snap Hook	Aluminum Locking Snap Hooks	2.8 lbs (1.3kg)	6' (1.8m)
233MAL/6FTGN	One	Choke-Off Loop	Aluminum Locking Snap Hook	1.3 lbs (0.6kg)	6' (1.8m)
233MRAL/6FTGN	One	Choke-Off Loop	Aluminum Locking Rebar Hook	2.1 lbs (1.0kg)	6' (1.8m)

Manyard II Shock-Absorbing Lanyards Contract 6 ft. [1.8m] to 4 ft. [1.2m] w/the unique stretchable design.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com