

Topgard® Protective Caps and Hats







Topgard Slotted Caps and Non-Slotted Hats are built for use by utilities, oil, gas and petrochemical, and other industries where head protection is needed in environments with higher temperature exposures.

- Classification:** Type I
- Application:** General purpose; elevated temperature¹
- Shell Material:** Polycarbonate
- Available Styles:** Slotted Cap; Non-Slotted Full-Brim Hat
- Sizes:** Standard (6½ – 8")
- Standards:** ANSI/ISEA Z89.1-2014 (Class E); CSA Z94.1-2005 (Class E)
- Certification:** Third-party by SEI
- Customization:** Imprinting and striping available



Topgard Protective Caps

Color	Topgard Slotted Cap (standard size)		
		w/ 1-Touch Suspension	w/ Fas-Trac® III Suspension
WHITE		454728	475385
YELLOW		454721	475378
GRAY		454722	475379
BLUE		454723	475380
ORANGE		454725	475382

Color	Topgard Slotted Cap (standard size)		
		w/ 1-Touch Suspension	w/ Fas-Trac® III Suspension
GREEN		454726	475383
RED		454727	475384
BRIGHT ORANGE		—	804396
WHITE W/LAMP BRACKET AND CORD HOLDER		448914	—



Topgard Cap with Fas-Trac III Suspension




¹Topgard Caps and Hats can withstand temperatures produced by radiant heat loads up to, but not exceeding, 275°F.


Because every life has a **purpose...**

Topgard Protective Hats

Color	Topgard Non- Slotted Full-Brim Hat (standard size)		
		w/ 1-Touch Suspension	w/ Fas-Trac III Suspension
WHITE		454719	475393
YELLOW		454712	475387
GRAY		454713	—
ORANGE		—	804397

Replacement Suspensions

HELMET TYPE (SIZE)	Suspension Type (4-point, unless otherwise noted)		
	Fast-Trac III	1-Touch	Swing Ratchet ¹
TOPGARD CAP OR HAT (STANDARD)			
	10153384	10061127	816648

FAS-TRAC III SWEATBAND ACCESSORY		10153518	<ul style="list-style-type: none"> • For use with MSA Fas-Trac® III Suspension • Optional, moisture-wicking and washable • Can be attached/replaced while suspension is assembled in helmet • Sold ONLY in packages of 10
----------------------------------	--	----------	---

▲ WARNING

Use only the indicated MSA suspension in your MSA helmet. Do not mix suspension sizes and helmet sizes (i.e., putting a standard sized suspension in a large helmet or any other mismatched combination). Do not use competitor suspensions in MSA helmets. Inspect your suspension frequently. Suspensions should be replaced every 12 months, regardless of inspection results. Replace immediately (along with the helmet), if an impact has occurred. Failure to follow these instructions will reduce the energy absorbing ability of the protective helmet to receive impact, and could result in serious injury or death.

Please contact MSA Customer Service at 1-800-MSA-2222 for details about Topgard helmets or other head protection or helmet accessory products. You can also visit us on the web at MSASafety.com.

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAsafety.com

U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone 01 800 672 7222
Fax 52 - 44 2227 3943

MSA International
Phone 724-776-8626
Toll Free 1-800-672-7777
Fax 724-741-1553

ID 0612-06-MC / June 2015

© MSA 2015 Printed in U.S.A.