



Arc-Rated Harnesses

Description

Custom safety features have been incorporated for the security and protection of utility and maintenance workers. Arc-Rated harnesses are made with Kevlar/Nomex webbing, Kevlar web loop and rescue loops and leather insulators under all hardware.

Materials

Webbing:	Kevlar/Nomex
Elastic Keepers:	Kevlar, Elastic
Thread (Stitching):	Kevlar, Polyester
Web Loop:	Kevlar
Rescue Loops:	Kevlar
Insulators:	Leather
Buckles:	Clear Chromate Finished Carbon Steel
Grommets:	Brass
Labels:	Valeron
Cam Buckle:	Glass-filled Nylon, Aluminum, Stainless Steel
Pivotlink:	Clear Chromate Finished Carbon Steel, Stainless Steel
Back, Belt, Shoulder Pads:	Kevlar, Urethane
Label Pack:	Evoprene, Nylon

Technical

Max. Working Load:	400lbs (181.4kg)
Webbing Min.Tensile:	7000lbs (31kN)
D-ring Min. Tensile:	5000lbs (22kN)
Buckle Min. Tensile:	4000lbs (18kN)

RKNARRL-QC



Certification

Meets stringent ASTM F887-05 Arc-Flash standards and all OSHA, ANSI and CSA requirements.

Miller Revolution Arc-Rated Harnesses with Kevlar/Nomex Webbing, Kevlar Web Loop and Leather Insulators under all hardware

Model	Size	Standard Features	Side D-Rings & Pad	Leg Strap Buckles	Rescue Loops	Special Features
RKNAR-QC/UBK	U	• Quick-Connect Chest Buckles	No	Quick-Connect	No	Leather insulators; web back D-ring
RKNAR-TB/UBK	U		No	Tongue	No	Leather insulators; web back D-ring
RKNAR-QC-BDP/UBK	U	• Cam Buckles	Yes	Quick-Connect	No	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNAR-TB-BDP/UBK	U	• ErgoArmor Back Shield	Yes	Tongue	No	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNARRL-QC/UBK	U	• Self-Contained Label Pack	No	Quick-Connect	Yes	Leather insulators; web back D-ring
RKNARRL-TB/UBK	U		No	Tongue	Yes	Leather insulators; web back D-ring
RKNARRL-QC-BDP/UBK	U		Yes	Quick-Connect	Yes	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNARRL-TB-BDP/UBK	U	• Web Finalis	Yes	Tongue	Yes	Leather insulators; web back D-ring; removable belt; side D-rings & pad

For front D-ring vest-style option, add "FD" to the corresponding harness model number (Ex. RKNFD-QC/U)



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.