

PRODUCT SPECIFICATIONS

LiftTech 60' Winch

#7292

Features

- Personell winch for confined space entry and retrieval.
- Bi-directional brake for user safety and smooth operation.
- 11:1 mechanical advantage for ease of use.
- Includes bracket for mounting to #7274 tripod.

Material Specifications

- Housing /Drum:** *Aluminum alloy with Nylon cover.*
- Cable:** *3/16", 7x19 galvanized steel*
- Connector Gates:** *Alloy Steel; Min. 3,600 lb. front and side load.*

Performance Specifications

- Tensile Strength:** *Min. 3,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *N/A*
- Average Arrest Force:** *N/A*
- Max. Elongation:** *N/A*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*
Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Not for fall arrest - for confined space entry and retrieval only.



WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.