

# PRODUCT SPECIFICATIONS

## 60' DuraTech 3-Way Recovery Unit

#7285

### Features

- Fully functional SRL with inertial brake.
- Includes rescue winch for use in confined space rescue/evacuation.
- Includes load-indicating swivel carabiner.
- Includes bracket for attachment to #7275 tripod.

### Material Specifications

- Housing/drum:** *Aluminum alloy.*
- Cable:** *3/16', 7x19 galvanized steel.*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs. front and side load.*

### Performance Specifications

- Tensile Strength:** *Min. 3,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *2 feet*
- Average Arrest Force:** *Less than 900 lbs.*
- Max. Elongation:** *42 inches*

### Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*  
*Z359.1-2007*

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use in overhead applications - maximum allowable freefall = 2 feet!
- Not for use in in confined space entry and retrieval - for rescue only.



WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.