

Gillette GPE-65H 6500 Watt Portable Gas Generator

MODEL GPE-65H

60 HERTZ

Heavy Duty, long lasting portable power for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then **GEN-PRO** is the right choice for you. These generator sets driven by **EPA Certified** engines and fuel systems are made for the tough jobs when you need the reliability, and good clean electrical energy. This is exactly what you get, when you choose **GEN-PRO**, because of it's many heavy duty & exclusive features.



| GENERATOR MODEL | GPE-65H |
|-------------------------|---|
| MAX. KW @ 1 PH. | 6.5 |
| PRIME KW @ 1 PH. | 6.0 |
| PRIME AMPS @ 120 V. | 50 |
| PRIME AMPS @ 240 V. | 25 |
| GENERATOR REGULATION | 5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS. |
| FREQUENCY REGULATION | 5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING |
| "KLEEN-POWER"™ | ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL GEN- PRO GEN-SETS |
| ENGINE MODEL (WARRANTY) | HONDA GX390 O.H.V. (3 YEARS) |
| ENGINE START METHOD | ROPE RECOIL ONLY |
| ENGINE HP @ 3600 RPM | 13 HP |
| ENGINE DISPLACEMENT | 1 CYLINDER, 23.7 CU. IN. (390 CC) |
| ENGINE AIR CLEANER | HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS |
| ENGINE FUEL TANK | 2.6 GAL. (10 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE |
| ENGINE OIL SYSTEM | FORCED SPLASH |
| LOW OIL PROTECTION | AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL |
| db(A) AT 7 METERS | 77 |
| 3/4 LOAD RUN TIME (HRS) | 3.1 |
| FUEL USE, GAL/LTR/HR | 0.84 / 3.17 |
| MOTOR START POWER | 2 HP, CODE G ELECTRIC MOTOR |
| CRANE PICK-UP HOOK | OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET |
| 2-WHEEL DOLLY KIT | OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS |
| MAINLINE CB | EXCLUSIVE GROUND FAULT CIRCUIT INTERRUPTION (GFCI) ON 120 V. RECEPTACLES AND NOW INCLUDING 240 V. RECEPTACLES, PROVIDING A COMPLETE OPERATOR SHOCK PROOF PROTECTION |
| HOUR METER | RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER |
| POWER RECEPTACLES | (4) NEMA 5-15R 120 VOLTS, AND (1) L-14-30R 240 VOLTS RECEPTACLES |
| PROTECTIVE ROLL FRAME | RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET |
| LENGTH, INCHES | 30.5 |
| WIDTH, INCHES | 24 |
| HEIGHT, INCHES | 23 |
| SHIP WEIGHT, LBS. | 220 |
| CU. FEET SHIP BOX | 12 |