

Gillette GPE-75H 7500 Watt Portable Gas Generator

MODEL GPE-75H

60 HERTZ

Heavy Duty, long lasting portable power for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then **GEN-PRO** is the right choice for you. These generator sets driven by **EPA Certified** engines and fuel systems are made for the tough jobs when you need the reliability, and good clean electrical energy. This is exactly what you get, when you choose **GEN-PRO**, because of it's many heavy duty & exclusive features.



GENERATOR MODEL	GPE-75H
MAX. KW @ 1 PH.	7.5
PRIME KW @ 1 PH.	6.5
PRIME AMPS @ 120 V.	54
PRIME AMPS @ 240 V.	27
GENERATOR REGULATION	5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.
FREQUENCY REGULATION	5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING
"KLEEN-POWER"™	ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL GEN- PRO GEN-SETS
ENGINE MODEL (WARRANTY)	HONDA GX390 O.H.V. (3 YEARS)
ENGINE START METHOD	ROPE RECOIL ONLY
ENGINE HP @ 3600 RPM	13 HP
ENGINE DISPLACEMENT	1 CYLINDER, 23.7 CU. IN. (390 CC)
ENGINE AIR CLEANER	HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS
ENGINE FUEL TANK	2.6 GAL. (10 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE
ENGINE OIL SYSTEM	FORCED SPLASH
LOW OIL PROTECTION	AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL
db(A) AT 7 METERS	78
3/4 LOAD RUN TIME (HRS)	2.7
FUEL USE, GAL/LTR/HR	0.95 / 3.56
MOTOR START POWER	2 1/2 HP, CODE G ELECTRIC MOTOR
CRANE PICK-UP HOOK	OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET
2-WHEEL DOLLY KIT	OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS
MAINLINE CB	EXCLUSIVE GROUND FAULT CIRCUIT INTERRUPTION (GFCI) ON 120 V. RECEPTACLES AND NOW INCLUDING 240 V. RECEPTACLES, PROVIDING A COMPLETE OPERATOR SHOCK PROOF PROTECTION
HOUR METER	RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER
POWER RECEPTACLES	(4) NEMA 5-15R 120 VOLTS, AND (1) L-14-30R 240 VOLTS RECEPTACLES
PROTECTIVE ROLL FRAME	RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET
LENGTH, INCHES	30.5
WIDTH, INCHES	24
HEIGHT, INCHES	23
SHIP WEIGHT, LBS.	227
CU. FEET SHIP BOX	12