

Meeting & Exceeding Customers' Value Propositions

Applications



Driving Factor



Attics



Savings in Transportation Time and Fuel Costs *offsets* Larger systems' increased production rate



Dense Pack & Wall Spray



Precision with Pressure / Product Flow

System Comparisons



Driving Factor

Cost of Ownership



5 year cost ~ 1/5 to 2/3 that of competitive systems

Portability & Transport



Portable -- No Specialized Equipment (i.e. dedicated truck) Requirements

Energy Consumption



Powered by clean, quiet electric motors v. gas or diesel with associated pollution

Maintenance



Minimal. Direct Drive System gear lubrication changed once/year; Seals changed only after 300 hours

[Intec Turbo Force Hp3 40009 00 Insulation Blowing Machine](#)
[Intec Turbo Force Hp3 40008 00 Insulation Blowing Machine](#)
[Intec Turbo Force Hp3 40010 00 Insulation Machine Canada](#)
[Intec Turbo Force Hp3 40011 00 Insulation Machine Canada](#)
[Intec Turbo Force Hp3 40012 00 Insulation Machine Canada](#)
[Intec Turbo Force Hp3 40005 00 Insulation Machine Canada](#)
[Intec Turbo Force Hp3 40006 00 Insulation Machine Canada](#)
[Intec Turbo Force Hp3 40007 00 Insulation Machine Canada](#)

System Comparisons

Customers value...

| System | | cellulose | | | | | fiberglass | | | | | | |
|---|-----------|-------------|--------------|---------------------|---|---------------------|---|--------------------------|---|---------------------|---|--------------------------|-----------|
| | | Portability | Weight (lbs) | Hopper size (cu ft) | Install Time (minutes) R19 in 100sq ft attic | Production (lbs/hr) | Production (bags/hour @ 25lb/bag) Dense Pack Retrofit ^{1,2} | Hopper Capacity (# bags) | Install Time (minutes) R19 in 100sq ft attic | Production (lbs/hr) | Production (bags/hour @ 30lb/bag) Dense Pack Retrofit ² | Hopper Capacity (# bags) | |
| Cyclone ^A | excellent | 142 | 5.3 | 51 | 800 | 32 | no | 1/2 | 74 | 204 | 7 | yes | 1/3 |
| FORCE/1 ^A | above avg | 177 | 4.5 | 76 | 540 | 22 | no | 1/2 - 1 | 81 | 187 | 6 | yes | 1/3 |
| FiberForce ^{A,B} <small>tall hopper avail</small> | excellent | 150 | 9 | 39 | 1050 | 42 | no | 1-2 | 38 | 400 | 13 | yes | 1/2 |
| WASP ^C | above avg | 280 | 10 | 23 | 1750 | 70 | yes | 1 ⁺ | 30 | 475 | 16 | yes | 1/2 |
| FORCE/2 ^C | average | 283 | 9 | 18 | 2280 | 91 | yes | 1-2 | 27 | 615 | 21 | yes | 1/2 |
| FORCE/3 ^C | above avg | 350 | 11.5 | 16 | 2520 | 101 | yes | 1 | 15 | 1350 | 45 | yes | 1/2 - 3/4 |
| TURBO FORCE | average | 380 | 17 | 18 | 2475 | 99 | yes | 2-3 | 19 | 900 | 30 | yes | 1/2 - 1 |

Notes:

1 Department Of Energy requires outlet pressure >=2.9psi (80" of water) for cellulose Dense Pack to achieve 3.5lbs/cu-ft density.

2 Dense Pack capability provides installers with additional market opportunities & resulting profit.

A Systems come standard with 100' 2-1/2" hose, connectors & clamps, & LED power cords.

B All-fiber configuration with slide gate & tall hopper.

C Systems come standard with LED power cords.

Versatile & Reliable Operation with Industry Leading Return on Investment